

Flor-Color® Premium Application Steps and Tips

A product of Diamatic and Diamatic Management Services

KEEP FROM FREEZING.

See PDS directions and MSDS for complete usage and safety instructions.

COVERAGE RATE

300-600 sq. ft. per gallon

INTRODUCTION

Flor-Color® Premium is a colored and colorable lithium-based densifier for use in the **Ultra-Flor®** Color Specification. For your color choice, select a color from the Diamatic color chart. **Flor-Color® Premium** is intended for outdoor and indoor use and is UV resistant.

APPLICATION INSTRUCTIONS

1. Outdoor Installation – No Polish

- I. Power Wash Surface to remove surface grit and grime.
- II. Apply pigment-colored **Flor-Color® Premium** densifier using a low pressure sprayer and a clean, stiff bristled broom. Spray each coat in a fine mist with full coverage. Broom in the **Flor-Color® Premium** after being sprayed down, and continue to broom area until dry to prevent any streaks from forming.
- III. Allow to dry for 30 minutes.
- IV. Apply a second coat of **Flor-Color® Premium** using a sprayer and a clean, stiff bristled broom. Spray each coat in a fine mist with full coverage. Broom in the **Flor-Color® Premium** 10 seconds after being sprayed down, and continue to broom area until dry to prevent any streaks from forming. If concrete has not reached the desired color, then apply additional coats following the same procedures listed in this step. If a mottled look is desired, don't broom in these additional applications.
- V. DO NOT ALLOW puddles to form.
- VI. Allow to dry for 30 minutes.
- VII. For a guarded surface, Apply **Flor-Guard® Outdoor**. Please refer to the Application instructions for **Flor-Guard® Outdoor**.

2. Indoor Application – Polished Surface

- I. Install Ultra-Flor to a maximum of a 400 Grit Finish.
- II. Clean surface to remove all dirt, grit and grime.
- III. Apply pigment-colored **Flor-Color® Premium** densifier using a low pressure sprayer and a clean, microfiber mop. Spray each coat in a fine mist with full coverage. Mop in the **Flor-Color® Premium** after being sprayed down, and continue to mop area until dry to prevent any streaks from forming.
- IV. Allow to dry for 30 minutes.
- V. Apply a second coat of **Flor-Color® Premium** using a sprayer and a clean, microfiber mop. Spray each coat in a fine mist with full coverage. Mop in the **Flor-Color® Premium** 10 seconds after being sprayed down, and continue to mop area until dry to prevent any streaks from forming. If concrete has not reached the desired color, then apply additional coats following the same procedures listed in this step. If a mottled look is desired, don't broom in these additional applications.
- VI. DO NOT ALLOW puddles to form.

- VII. Allow to dry for 30 minutes.
- VIII. For a guarded surface, Apply **Flor-Finish**. Please refer to the Application instructions for **Flor-Finish**.

PROFESIONAL USE ONLY

Must be applied by **Diamatic Management Services (DMS)** trained or certified contractors and/or licensed field service specialists.

CLEAN UP

Use water to clean tools and equipment. Treatment is environmentally friendly and requires no special or hazardous disposal methods.

HEALTH AND SAFETY PRECAUTIONS

Flor-Color® Premium DSB, Densifying Stain Base for outdoor use is an aqueous lithium silicate solution that uses proprietary compounds. The treatment is alkaline and may cause eye and skin irritation. **KEEP OUT OF THE REACH OF CHILDREN**. Do not take internally. Avoid prolonged contact with skin. Avoid ingestion of material. If swallowed, do not induce vomiting – Call physician. Avoid contact with eyes. Protective clothing is recommended. Protective goggles are recommended in case of splashing. If splashed in eyes, wash immediately with clean water and call physician if irritation persists. Contact areas should be thoroughly washed with soap and water. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet. **Flor-Color® Premium DSB** will bond to most surfaces - immediately wash off over spray with water and mild detergent. **CAUTION:** Surfaces wet with **Flor-Color® Premium DSB** may be slippery.

Warranty

This instruction is condensed and should not be considered complete. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.